

i-Touch V15G



New Style Interactive 15" Through-Glass kiosk with 1Ghz VIA, Panel PC

Our innovative new design for this Through Glass kiosk, means that there is no installation. It is not necessary for you to have the through glass sensor bonded to your window, and the kiosk unit needn't be permanently installed in one location.

The units design means that it has a slight forward tilt, so that you simply drop the unit in place, against your window, and members of the public have access to all of your products and services outside of normal business hours.

The new styled v15G kiosk unit allows full flexibility, while maintaining a wealth of functionality. Weight: 20Kg

Physical Specifications

Dimensions (WxHxD) **500mm x 1520mm x 250mm** Operating

Weight **20Kg**

Environment

2 + 2 Watts

-25 to 40 Degress

Audio RTB Warranty

2 + 2 watts 1 Year

Build Material

Powder Coated Steel and

Plexiglass

Fixing Details TE

Manufacturer Future Generation

Controller Model Colours Titan TTN3-ADA-LQ150X1LGN2

16.7 Million

Viewing Angle Control Type TBA OSD 1024x768

Contrast 350:1

Resoloution Cable Connector

15 pin D-Sub / Dvi

Brightness 260 Cd Backlight 35,000

ght **35,000 Hours Typical**

Power Specifications

Power Supply 210-240 Volt AC Power Consumption 40 Watts Normal

Power Rating 80 watts

PC Specifications

VIA 1GHz

Processor or PentiumMemory 256mb

M 1.6GHz

Hard Disc Drive 40Gb

Special Comments

Dimensions of this unit are for stand shown. This stand can be designed to suit your requirements, whereby your defined dimensions would be applicable.

Meets DDA Requirements



i-Touch V15G Pictures















