





Slim-Line Metal Floor standing / Wall Mount kiosk with 15" screen

The V32 is designed to be used as either a Wall Mounted, Desktop or Floor Standing kiosk. The unit is constructed from powder coated steel, and built around standard nonproprietary PC technology.

As well as its wide application range, the most unique feature is the interchangeable option panels, which provide total flexibility in the configuration and functionality. This enables the same unit to be used in one of the three different configurations (Wall/Desk/Floor) to suit all types of environments, while maintaining synergy of product, especially where high traffic and durability is a requirement. The Kiosk houses a video camera for conferencing or monitoring purposes and for unattended or external use a bullet proof TFT screen and anti vandalism keyboard can also be fitted.

Physical Specifications

Dimensions (WxHxD) Weight) TBA x TBA x TBA TBA	<i>Operating Environment Audio RTB Warranty Build Material Fixing Details</i>	Powder Coated Steel
<i>Manufacturer Viewing Angle Control Type Resoloution</i>	Future Generation TBA OSD 1024x768	Controller Model Colours Contrast Brightness	Titan TTN3-ADA- LQ150X1LGN2 16.7 Million 350:1 260 Cd
Cable Connector	15 pin D-Sub / Dvi	Backlight	35,000 Hours Typical

Power Specifications

Power Supply	210-240 Volt AC
Power Consumption	40 Watts Normal
Power Rating	80 watts

PC Specifications

Processor	Pentium 4 (2.8ghz)	256mb
Hard Disc Drive	80Gb	

Special Comments Meets DDA Requirements



i-Touch V32 Pictures

