



Slim-Line Metal and Glass Floor standing / Desk / Wall Mount kiosk with 15" screen

The V31 is designed to be used as either a Wall Mounted, Desktop or Floor Standing kiosk. The unit is constructed from powder coated steel and, when floor standing, utilises lit edge plastics below the main body for visual effect.

As well as its wide application range, the most unique feature is the ability to simply fix the unit to a suitable wall, or use the base with poles to convert this kiosk to a floor standing unit. The v31 also offers interchangeable option panels, which provide total flexibility in the configuration and functionality. This enables the same unit to be used in many different configurations to suit all types of environments, while maintaining synergy of product, especially where high traffic and durability is a requirement. The Kiosk houses a video camera for conferencing or monitoring purposes and for unattended or external use a bullet proof TFT screen can also be fitted.

Physical Specifications

Dimensions (WxHxL Weight	D) TBA x TBA x TBA TBA	<i>Operating Environment Audio RTB Warranty</i>	-25 to 40 Degress 2 + 2 Watts 1 Year	
		Build Material	Powder Coated Steel and Plexiglass TBA	
		Fixing Details		
Manufacturer	Future Generation	Controller Model	Titan TTN3-ADA- LQ150X1LGN2	
Viewing Angle Control Type Resoloution Cable Connector	TBA OSD 1024x768 15 pin D-Sub / Dvi	Colours Contrast Brightness Backlight	16.7 Million 350:1 260 Cd 35,000 Hours Typical	

Power Specifications

Power Supply	210-240 Volt AC
Power Consumption	40 Watts Normal
Power Rating	80 watts

PC Specifications

Processor	Pentium 4 (2.8ghz)	256mb
Hard Disc Drive	40Gb	

Special Comments Meets DDA Requirements



i-Touch V31 Pictures







